



RADIO REMOTE STANDARD

911C/2S

Lbs	21160*	9440	6260	4860	3440	2450	1760	1340
ft'in"	3'3"	7'3"	11'1"	14'2"	20'2"	26'7"	33'6"	40'4"

911C/3S

Lbs	20410*	9080	5860	4540	3170	2450	1760	1340
ft'in"	3'3"	7'3"	11'5"	14'7"	20'6"	26'7"	33'6"	40'4"

911C/4S

Lbs	19780*	8840	5520	4250	2910	2200	1760	1340
ft'in"	3'3"	7'3"	11'9"	14'1"	20'1"	26'1"	33'6"	40'4"

911C/5S

Lbs	19310*	8640	5250	4030	2730	2030	1610	1340
ft'in"	3'3"	7'3"	12'1"	15'3"	21'2"	27'3"	33'4"	39'10"

*) Portata teorica - Theoretical lifting capacity

C= Retractable jib, for high load application

MODELLI MODELS	MOMENTO LIFTING MOMENT	SBRACCIO ORIZ. HORIZ. EXTENSION	PORTATA AL MAX. SBRACCIO MAX. REACH LIFTING CAPACITY	ANGOLO DI ROTAZIONE SLEWING ANGLE	PESO WEIGHT	DIMENSIONE DIMENSION
	ft Lbs	ft'in"	Lbs	°	Lbs	inches WxHxD
911C/2s	69400	20'2"	3440	405	2890	98x86x26
911C/3s	-	26'7"	2450	405	3100	98x86x26
911C/4s	-	33'6"	1760	405	3300	98x86x26
911C/5s	-	39'10"	1340	405	3450	98x86x30