



924C/2S

Lbs	43650	19400	12280	9770	7010
ft'in"	3'3"	7'5"	11'9"	14'11"	21'0"

924C/3S

Lbs	42960	19090	11840	9370	6670	5170	3970	3060	2390
ft'in"	3'3"	7'5"	11'10"	15'0"	21'2"	27'6"	33'10"	40'9"	47'7"

924C/4S

Lbs	41890	18620	11570	9040	6330	4870	3940	3030	2370	1840
ft'in"	3'3"	7'5"	11'9"	14'11"	21'1"	27'6"	33'10"	40'9"	47'7"	54'6"

924C/5S

Lbs	40680	18080	11130	8600	5990	4480	3570	3030	2340	1840	1410
ft'in"	3'3"	7'5"	12'0"	15'3"	21'4"	27'9"	34'2"	40'9"	47'7"	54'6"	61'4"

924C/6S

Lbs	39680	17640	10800	8420	5750	4230	3330	2670	2250	1760	1410	1210
ft'in"	3'3"	7'5"	12'4"	15'6"	21'8"	28'1"	34'5"	41'0"	47'7"	54'6"	61'4"	68'3"

*) Portata teorica - Theoretical lifting capacity

C= Retractable jib, for high load application

MODELLI MODELS	MOMENTO LIFTING MOMENT	SBRACCIO ORIZ. HORIZ. EXTENSION	PORTATA AL MAX. SBRACCIO MAX. REACH LIFTING CAPACITY	ANGOLO DI ROTAZIONE SLEWING ANGLE	PESO WEIGHT	DIMENSIONE DIMENSION
	ft Lbs	ft'in"	Lbs	°	Lbs	inches WxHxD
924C/2s	155500	21'0"	7010	410	5840	100x92x41
924C/3s	-	27'6"	5170	410	6170	100x92x41
924C/4s	-	33'10"	3940	410	6430	100x92x41
924C/5s	-	40'9"	3030	410	6750	100x92x41
924C/6s	-	47'7"	2250	410	6970	100x92x41