



**Amco Veba 809T / 909T RRS - 7 tm available with up to 4 hydraulic extensions**

*Easy to use*

By having one less function and simpler geometry, the crane is easier to stow, unstow, and use. This makes it very suitable for occasional operators, companies with many operators, and for rental companies.

*Light*

We omit the first boom found on an articulated version, as well as the offset second boom. Instead, we use an inline boom with extensions. This reduces the weight of the crane.

*Compact*

Thanks to the design a "T" crane takes up less space on the chassis. The body can be built longer to add space for cargo.



REACH @ CAPACITY						
<b>2S</b>	Lbs	7280	4250	2980	2310	*1610
	ft'in"	8'4"	13'11"	19'8"	24'3"	30'5"
<b>3S</b>	Lbs	7140	4100	2810	2140	*1650
	ft'in"	8'4"	13'11"	19'8"	25'5"	30'5"
<b>4S</b>	Lbs	7050	3990	2680	2010	1600
	ft'in"	8'4"	13'11"	19'8"	25'5"	31'4"
* Manually extendable extension optional						

SPECIFICATIONS	2S	3S	4S
Number of Extensions	2-Hydraulic	3-Hydraulic	4-Hydraulic
Crane Rating (ft. lbs.)	60,800	60,800	60,800
Max. Horizontal Reach - hydraulic	19'8"	25'5"	31'4"
Max. Vertical Reach - hydraulic	30'10"	36'9"	42'8"
Max. Capacity (lbs.)	2310	2140	1600
Crane Weight (lbs.)	2620	2800	2940
Crane Dimensions	93" x 91" x 24"	93" x 91" x 24"	93" x 91" x 24"
Mounting Space	77" x 7'8" x 1'11"	77" x 7'8" x 1'11"	77" x 7'8" x 1'11"
Slewing Angle (degrees)	395	395	395
Oil Tank Capacity (gallons)	15.9	15.9	15.9
Max. oil flow (gpm)	5.3	5.3	5.3
Max. working pressure (psi)	3626	3626	3626
Outrigger Extension	15'6"	15'6"	15'6"

STANDARD FEATURES
Dual Controls
Hexagonal section extensions
Independent extension cylinders
Designed in accordance with EN12999
Fixed stabilizer cylinders
Flanged Valves
SAE and JIC fittings
One year warranty

ACCESSORIES
Radio Remote Control
Manual extensions
Turning stabilizers
Supplementary element activation
Winch
Remote Control
Outrigger with hydraulic extension
Load limiting device

