











702T/1S	
Lbs	4010* 2190 1280 840
ft'in"	3'3" 5'9" 10'3" 15'4"
702T/2S	
Lbs	4120* 2190 1280 840 620
ft'in"	3'3" 6'0" 10'7" 15'5" 20'6"
703T/1S	
Lbs	6750* 3860 2010 1320
ft'in"	3'3" 5'9" 10'4" 15'2"
703T/2S	
Lbs	6610* 3590 1940 1280 930
ft'in"	3'3" 6'0" 10'7" 15'5" 20'6"
705T/2S	
Lbs	9060* 4630 2560 1650 1210
ft'in"	3'3" 6'5" 10'11" 16'3" 21'5"
705T/3S	
Lbs	8910* 4370 2430 1540 1210 880
ft'in"	3'3" 6'8" 11'3" 16'6" 21'5" 26'3"
807T/2S	
Lbs	15210* 7390 4100 2710 1900 1410
ft'in"	3'3" 6'9" 11'11" 17'4" 23'0" 28'11"
807T/3S	
Lbs	14990* 6940 3860 2540 1830 1340
ft'in"	3'3" 7'1" 12'3" 17'8" 23'4" 29'3"

*) Portata teorica - Theoretical lifting capacity

MODELLI MODELS	MOMENTO LIFTING MOMENT	SBRACCIO ORIZ. HORIZ. EXTENSION	PORTATA AL MAX. SBRACCIO MAX. REACH LIFTING CAPACITY	ANGOLO DI ROTAZIONE SLEWING ANGLE	PESO WEIGHT	DIMENSIONE DIMENSION
	ft Lbs	ft'in"	Lbs	°	Lbs	inches WxHxD
702T/1S	13500	10'3"	1280	370	980	76x67x16
702T/2S	-	15'5"	840	370	1080	76x67x16
703T/1S	22100	10'4"	2010	370	980	76x67x16
703T/2S	-	15'5"	1280	370	1080	76x67x16
705T/2S	29700	16'3"	1650	370	1420	80x76x18
705T/3S	-	21'5"	1210	370	1530	83x76x18
807T/2S	49900	17'4"	2710	370	2070	90x79x21
807T/3S	-	23'4"	1830	370	2250	91x79x21