















<b>809T/2S</b>		Lbs ft'in"	18520* 3'3"	7280 8'4"	4250 13'11"	2980 19'8"	2310 24'3"	1610 30'5"		
<b>809T/3S</b>		Lbs ft'in"	18300* 3'3"	7140 8'4"	4100 13'11"	2810 19'8"	2140 25'5"	1650 30'5"		
<b>809T/4S</b>		Lbs ft'in"	18080* 3'3"	7050 8'4"	3990 13'11"	2680 19'8"	2010 25'5"	1600 31'4"		
<b>811T/2S</b>		Lbs ft'in"	22490* 3'3"	8950 8'4"	5290 13'11"	3680 19'8"	2870 24'3"	2140 30'5"		
<b>811T/3S</b>		Lbs ft'in"	22490* 3'3"	8820 8'4"	5110 13'11"	3530 19'8"	2700 25'5"	2140 30'5"		
<b>811T/4S</b>		Lbs ft'in"	22270* 3'3"	8710 8'4"	5020 13'11"	3420 19'8"	2580 25'5"	2070 31'4"		
<b>815T/2S</b>		Lbs ft'in"	31530* 3'3"	14000 7'5"	7540 13'3"	5040 19'5"	3530 26'2"	2650 33'0"	2050 40'2"	
<b>815T/3S</b>		Lbs ft'in"	30950* 3'3"	13230 7'8"	7190 13'7"	4700 19'9"	3420 26'3"	2560 33'0"	1960 40'2"	1590 47'1"
<b>815T/4S</b>		Lbs ft'in"	30950* 3'3"	12790 7'11"	6890 13'10"	4450 20'0"	3170 26'6"	2480 33'0"	1940 40'2"	1540 47'1"
<b>817T/2S</b>		Lbs ft'in"	34170* 3'3"	14330 7'5"	7780 13'3"	5270 19'5"	3730 26'2"	2840 33'0"	2200 40'2"	
<b>817T/3S</b>		Lbs ft'in"	33070* 3'3"	13670 7'8"	7410 13'7"	4890 19'9"	3620 26'3"	2730 33'0"	2140 40'2"	1740 47'1"
<b>817T/4S</b>		Lbs ft'in"	33070* 3'3"	13230 7'11"	7100 13'10"	4650 20'0"	3370 26'6"	2650 33'0"	2090 40'2"	1700 47'1"

\*) Portata teorica - Theoretical lifting capacity

MODELLI MODELS	MOMENTO LIFTING MOMENT	SBRACCIO ORIZ. HORIZ. EXTENSION	PORTATA AL MAX. SBRACCIO MAX. REACH LIFTING CAPACITY	ANGOLO DI ROTAZIONE SLEWING ANGLE	PESO WEIGHT	DIMENSIONE DIMENSION
	ft Lbs	ft'in"	Lbs	°	Lbs	inches WxHxD
809T/2s	60800	19'8"	2980	405	2580	93x91x24
809T/3s	-	25'5"	2140	405	2760	93x91x24
809T/4s	-	31'4"	1600	405	2900	93x91x24
811T/2s	73800	19'8"	3680	405	2620	93x91x24
811T/3s	-	25'5"	2700	405	2800	93x91x24
811T/4s	-	31'4"	2070	405	2940	93x91x24
815T-2s	103400	19'5"	5040	380	3440	98x99x31
815T-3s	-	26'3"	3420	380	3730	98x99x31
815T-4s	-	33'0"	2480	380	3970	99x99x31
817T-2s	112100	19'5"	5270	380	3530	98x99x31
817T-3s	-	26'3"	3620	380	3840	98x99x31
817T-4s	-	33'0"	2650	380	4080	99x99x31